



Case:  
Heavy duty vacuum formed ABS.

A/C Connections:  
#12 MIO male fitting and #10 female O-ring nut into expansion valve with #6 male O-ring connection.

Heater Hose Connections:  
2 x 5/8"

Air Ducts:  
4 x 2-1/2" outlets.

Coil:  
Copper tube and fin combination cool and heat, 20,000 BTU cool/ 22,000 BTU heat.

Spal Blower Specifications:  
High-output blower assembly, 450 CFM @ 13.5 VDC, 10 amp draw. 3-speed blower resistor included.

PARTS LIST:

PART NUMBER	DESCRIPTION	Quantity
ACPLA001B	Max Air 1 Case Bottom	1
ACPLA001T	Max Air 1 Case Top	1
ACPLA001H	Max Air 1 Hose Outlet	1
ACMTR001	Spal Dual Blower	1
ACBKT014	Max Air 1 Side Anchor	2
ACBKT015	Max Air 1 Side Bracket	2
ACBKT016	Max Air 1 Motor Plate	2
ACHDW025	Drain Tube	2
ACFOA012	Foam Kit	1
ACFOA011	Foam, Spal 39 Blower gasket	2
ACFOA003	#7 PVC foam 1/8" x 1/2"	4 ft.

PART NUMBER	DESCRIPTION	Quantity
ACHDW002R	Tape, cork	1 ft.
ACCOI008	AC Heat Coil	1
ACHDW008	O-ring #8 Green	1
AC1007	Expansion Valve	1
ACFIT002	Expansion Valve screen	1
ACHDW020	Bolt 1/4 20 x 1/2	4
ACUNI001LAB	Max Air 1 Label	1
ACHDW018	Screw, #8 X 1/2" PPH BLK	13
ACHDW019	Screw, #8 X 5/8" PPH BLK	8
ACHDW021	Pop rivet 5/32"	6
ACWIR003	Blower resistor harness	1

Notes:  
Includes wiring harness, expansion valve and mounting brackets.

DRAWN John Matlack	3/15/2017	Infinite Innovations		
CHECKED		TITLE		
QA		Max Air 1		
MATERIAL		Part #ACUNI001		
APPROVED		SIZE C	DWG NO MA1-1	REV
TOLERANCE		SCALE	SHEET 1 OF 1	