

22.0" Flush Wall-Mount LCD Monitor

Instruction Manual v1.0



Table of Contents

1.0	What is in the Box	Page	1
2.0	Key Features	Page	1
3.0	Electrical System Wiring	Page	2
4.0	Inputs-Outputs Cables	Page	2
5.0	Specifications	Page	3
6.0	Remote Control Functions & Menu Operation Instructions	Page	4

1.0

What is Included in the Box

Monitor and Wireless Remote Control

- 1.1 22.0" Wall Flush Mount LCD Monitor
- 1.2 Remote Eye with cable
- 1.3 Wireless Remote control



2.0

Key Features

- 2.1 22.0" LCD Screen
- 2.2 1080 HDMI Input
- 2.3 Single RCA Video Input
- 2.4 USB/SD card input
- 2.5 Metal Housed
- 2.6 Wireless Remote Control

22.0" Flush Wall-Mount LCD Monitor

Instruction Manual v1.0



3.0 Electrical System Wiring

- 3.1 Operating Voltage : 12.0 VDC
- 3.2 Power Consumption : 24.0 Watts
- 3.3 Current Draw : 2.0 Amps
- 3.4 Red Wire : IGN power +12 VDC
- 3.5 Green : +12 VDC trigger

4.0 Inputs-Outputs Cables

- 4.1 Video Input 1 : Yellow => RCA Connector (CVBS compatible)
- 4.2 Right Audio Input : Red RCA Connector
- 4.3 Left Audio Input : White RCA Connector
- 4.4 VGA Input : yes
- 4.5 HDMI Input : yes
- 4.6 USB Input 1 : yes (MP4, AVI Video Files)
- 4.7 USB Input 2 : yes (MP4, AVI Video Files)
- 4.8 SD Card Slot : yes - Side of Monitor (MP4, AVI Video Files)
- 4.9 IR Eye with Cable : For wireless remote control

Note : CVBS => Composite Video Baseband Signal

5.0 Specifications

5.1	LCD Screen Size	:	22.0"
5.2	Video System	:	NTSC / PAL
5.3	Widescreen	:	16 : 9
5.4	Resolution	:	1920 x 1080
5.5	Brightness	:	400 Nit
5.6	Contrast	:	500 : 1
5.7	Viewing Angle (R/LT/B)	:	85 / 85 / 80 / 80 degrees
5.8	Back Light Life	:	20,000 Hours

5.9 Video Input Signals

*	Video Input	:	Yellow RCA Connector (CVBS)
*	VGA Input	:	yes
*	HDMI Input	:	yes
*	USB 1 Input	:	yes (MP4 & AVI Video Files)
*	USB 2 Input	:	yes (MP4 & AVI Video Files)
*	SD Card Slot	:	yes - Side of Monitor (MP4 & AVI Video Files)

6.0 Audio Input Signals

*	Right Audio Input	:	Red RCA connector
*	Left Audio Input	:	White RCA connector

6.1	Operating Voltage	:	12 VDC
6.2	Current Draw	:	2.0 Amps @ 12 VDC
6.3	Power consumption	:	24.0 Watts
6.4	OSD (On Screen Display) Menu	:	yes
6.5	Mount Included	:	Yes - Pedestal Stand
6.51	Image Flip Function	:	Image Rotate
6.52	IR Eye for wireless remote	:	yes
6.53	Remote Control (Wireless)	:	Yes
6.54	Operating Temperature	:	0 C to +70 C degrees
6.55	Storage Temperature	:	-10 C to +70 C degrees

6.56 Dimensions

Height	:	12.9 "	=>	327.7 mm
Width	:	21.0 "	=>	533.4 mm
Depth	:	1.2 "	=>	30.5 mm

22.0" Flush Wall-Mount LCD Monitor

Instruction Manual v1.0

6.0 Remote Control Functions



N/A => Not Applicable



Power On/Off



Select Video Input



Select USB/SD



N/A



Up



N/A



Left



N/A



Right



N/A



Down



N/A



Exit (Go Back Menu)



N/A



Mute



N/A



Menu Settings



N/A