



Spal Blower Specifications:
 High-output blower assembly, 605 CFM @ 13.5 VDC, 14 amp draw. 3-speed blower resistor included.

Case:
 Heavy duty vacuum formed ABS.

A/C Connections:
 #12 MIO male fitting and #10 female O-ring nut into expansion valve with #6 male O-ring connection.

Heater Hose Connections:
 2 x 5/8"

Air Ducts:
 4 x 2-1/2" outlets.

Coil:
 Copper tube and fin combination cool and heat, 23,600 BTU cool/ 26,000 BTU heat.

PARTS LIST:

PART NUMBER	DESCRIPTION	Quantity
ACBKT005	Bkt blower motor all-sides/ext	2
ACPLA032R	Case top	1
ACPLA031R	Case bottom	1
ACPLA033R	Case front 4 duct outlet	1
ACCOI005H	Heater Coil	1
AC-FOA001	Die cut blower foam seal 1/8"	2
ACHDW018	Screw, #8 X 1/2" PPH BLK	13
ACHDW019	Screw, #8 X 5/8" PPH BLK	5
ACMTR002	Dual shaft motor assembly w/res	1

PART NUMBER	DESCRIPTION	Quantity
ACWIR003	Dual shaft mtr harness	1
ACBKT006	Bkt blower motor all-center/in	1
ACBKT007	Bkt blower motor all-sides/int	2
ACHDW021	Pop rivet 5/32"	14
ACBKT001	Bracket, unit mounting	2
ACFOA003	#7 PVC foam w/adhesive 1/8" x 1/2"	4 ft.
ACHDW002R	Tape, cork	1 ft.
ACUNI006LAB	Label Max Air	1

Notes:
 Includes wiring harness, expansion valve and mounting brackets.

DRAWN John Matlack	6/22/2016	Infinite Innovations		
CHECKED		TITLE Max Air 3 Part #ACUNI006H		
QA		SIZE C	DWG NO MA3-1	REV
MATERIAL		SCALE	SHEET 1 OF 1	
APPROVED				
TOLERANCE				